

MASK

Mask is a Coal tar based liquid for use in foot baths, on ground floors / soil floors, drains, etc.
 Mask has a dual purpose : It reduces microbes and is an excellent masking agent.
 Mask is widely used to remove stubborn germs from sinks, waste bins, and drains.
 Mask will stain surfaces when used at a high concentration.
 Product pH at a 1 % dilution is between 2.00 - 3.00.

Dilutions

Use at 1: 100 (10 ml/L) dilution with water depending on application requirements.
 Mix 1L Mask with 1L diesel to 100 L water as a reducing agent for ground and soil floors.
 Add 10ml Mask to 12Lt water, mix well and apply to surface by mop.
 Rinse treated surface thoroughly. Always use gloves and protective clothing.

GHS Identification:

Danger

UN 2927 Toxic Liquid Corrosive NOS



PPE

Gloves, Goggles, Personal Protective Clothing, Gumboots



First Aid

SKIN	EYES	INHALATION	ORAL
Remove/take off all contaminated clothing immediately. Rinse skin with water.	If in EYES rinse cautiously with water for several minutes, remove contact lenses if safe and easy to do. Continue rinsing, seek medical help.	If INHALED and breathing is difficult – remove person to fresh air and seek medical attention	Do NOT induce vomiting
			Drink water / milk / egg white
If skin irritation persists consult a doctor.	Consult a Doctor immediately		Consult a Doctor immediately

AVAILABLE IN

5Lt, 25Lt, 210Lt